



**ZHEJIANG CFMOTO POWER CO., LTD.**

No. 116, Wuzhou Road, Yuhang Economic Development Zone Hangzhou 311100, Zhejiang Province.

✉ [info@cfmoto.com](mailto:info@cfmoto.com)/[media@cfmoto.com](mailto:media@cfmoto.com)

🌐 [Global.cfmoto.com](http://Global.cfmoto.com)

📘 [CFMOTOOFFICIAL](#)

📷 [cfmotoofficial](#)

📺 [CFMOTO](#)

Copyright Zhejiang CFMOTO Power co., Ltd. 2021. All rights reserved. Photos are for illustrative purposes only. The vehicle configuration may be subject to change due to local laws and regulations in different countries and regions. Vehicle specifications are subject to change without notice. Imagery may not reflect most current product specifications. CFMOTO reserves the right to make improvements and/or design changes without any obligation to modify previously sold, assembled or fabricated equipment.



PRODUCT BROCHURE

**CFORCE 450**  
**CFORCE 520**





# UP YOUR GAME

EXPERIENCE MORE  
TOGETHER

## INTRODUCTION

With refinements in nearly every category, the newest generation CFORCE 450 and CFORCE 520 bring even more rugged capability to the CFMOTO ATVs. Infused with the right technology to work harder and smarter, the CFORCE 450 and 520 are outfitted for more utility performance than ever. With tighter turning radius, a stronger frame, even more suspension travel and comfort, increased loading capacity, the CFORCE 450 and 520 will take on your toughest tasks, and still be ready for fun when the work is done.

Whether you're moving equipment on your property or tending to the livestock, the CFORCE 450 and CFORCE 520 have the advanced features, accessories and all-day comfort to get the job done.





The new generation of CFORCE 450 and CFORCE 520 features all-over improvements for class-leading midsize utility ATV performance.

# PERFORMANCE UPGRADE

- ✔ Stronger than ever with **1350-lb** towing capacity
- ✔ **25%** tighter turning radius
- ✔ **50%** more front and rear rack loading capacity
- ✔ **30%** stronger and **10%** lighter frame
- ✔ **26%** more suspension travel
- ✔ **21%** more fuel capacity

\* The vehicle specifications may be subject to change due to local laws and regulations in different countries and regions



With two different sizes (short and long) for each model, the CFORCE 450 and CFORCE 520 offer the ideal solutions for the demands of your day.

**experience  
more  
together**







# CFORCE 450

## CFORCE 450



## CFORCE 450 L



CFMOTO answers the call of customers looking for an affordable, rugged and maneuverable midsize machine that's built tough with the CFORCE 450. Its quality starts with a high-strength steel-frame backbone, matched to a proven single-cylinder liquid-cooled SOHC engine and smooth CVT transmission.

The robust output of the 400cc engine, plush suspension travel, four hydraulic disc brakes, 24-inch AT tires, comfortable ergonomics and 1350-lb towing capability puts the CFORCE 450 on par with bigger brands in all aspects. Offering both one-up and two-up version adds to the versatility of this highly adaptable utility ATV.



# CFORCE 520 CFORCE 520 L



The 495cc engine of the CFORCE 520 adds more power and more possibilities to the agile ATV platform. Fortified with EPS, bigger torque and premium accessories such as RIDEVISION® LED lights, aluminum alloy wheels, and 25-inch AT tires bring its rugged capability to a new level.

Handguards, and interchangeable luggage racks with the CF-CONNECT quick-release system add comfort and convenience for longer rides and tougher tasks. Standard features like a remote-control 2500-lb winch and an array of available accessories make the CFORCE 520 an ideal machine to outfit for your adventure.





# NEW COLOR SCHEME

The look of the all-new CFORCE 450 and CFORCE 520 is BOLDER, yet the exterior retains its compact profile. Wheelbase remains the same, while the overall stance increases, giving the CFORCE 450 and 520 a more commanding presence.





# UP YOLO GAME







# MORE CAPABILITY INSIDE

## Lowest vibration in class

When it comes to long hours in the field, vehicle vibration is a critical factor that can wear you down. The CFORCE 450 and 520 have the lowest vibration in class across the entire torque range (vibration measured at handlebar grip, seat, and foot rests).

## 25% lower temperatures in low-rpm use

During sustained low-rpm use, engine temperatures can climb. But the CFORCE 450 and 520 are engineered for comfort throughout your work day. Revised radiator design and improved cooling mean leg area temperatures remain 25% lower than before.



EXPERIENCE MORE TOGETHER





# ALL-DAY COMFORT

## Rider-friendly ergonomics

New rider-friendly ergonomics place the handlebar higher and closer to the rider. A lower foot brake further improves body position, which is optimized for a more aggressive rider posture.



## More fuel capacity

The newly designed fuel tank is not only narrower to accommodate riders' position, either standing or sitting, with more leg space, it also provides more range with 17-liter fuel capacity, an increase of 3 liters.



## Foam seats

New foam material is used in the seats. Foam thickness increased by 40%. The backrest of the two-up vehicles also receive an increase in foam thickness, while also offering a wider waist brace for improved passenger comfort and stability.



The fuse box, coolant and brake fluid are easily accessible under the front hood.

The CVT assembly cover is all one piece, only needing removal for belt replacement.



The one-piece fuel tank cover can be removed without tools, making access to the air filter easier than ever.

The rear storage has 10.5-liter capacity, and easy access to stow gear.

# GREATER CONVENIENCE



## CFORECE 450

3.5-inch digital gauge

All-new user interface, clearly displaying key vehicle information with better readability.

## CFORECE 520

5-inch digital display

Full-screen backlight for all-day clarity.



# VARIETY ACCESSORIES

Get outfitted for work or adventure (or both!) with accessories that are ready to bolt right up to the CFORCE 450 and 520. A wide variety of CFMOTO luggage accessories, bumpers and bash plates have been developed to seamlessly integrate with your new CFORCE 450 and 520 utility ATVs.





		<b>CFORCE 450</b>		<b>CFORCE 450L</b>	
		<b>Homologation 167</b>	<b>Homologation 168</b>	<b>Homologation 167</b>	<b>Homologation 168</b>
<b>DIMENSIONS CAPACITIES</b>	Length x Width x Height	2186 x 1125 x 1150 mm	2186 x 1125 x 1150 mm	2386 x 1125 x 1205 mm	2386 x 1125 x 1205 mm
	Wheelbase	1260 mm	1260 mm	1460 mm	1460 mm
	Ground Clearance	250 mm	250 mm	250 mm	250 mm
	Minimum Turning Diameter	5.6m	5.6m	6.5m	6.5m
	Approach Angle	83°	83°	83°	83°
	Payload Capacity	240 kg	170 kg	240 kg	240 kg
	Curb Weight	336 kg	342 kg	350 kg	356 kg
	Hitch Towing Rating(trailer without brakes)	260 kg	150 kg	260 kg	150 kg
	Hitch Towing Rating(trailer with brakes)	612 kg	612 kg	612 kg	612 kg
	Fuel Capacity	17 L	17 L	17 L	17 L
<b>ENGINE</b>	Type	400cc, single cylinder, liquid-cooled, 4 stroke, SOHC			
	Fuel Delivery	EFI			
	Transmission	CVT, L/H/N/R/P			
	Drive System	2WD/4WD/4WD Lock			
	Power	31 hp			
<b>CHASSIS</b>	Front Suspension	Independent Dual A-Arm, 190mm travel			
	Rear Suspension	Independent Dual A-Arm, 225mm travel			
	Brakes	Four-wheels hydraulic side break + rear wheel side parking			
	Wheels	Front: 12x6.0. Rear: 12x7.5			
	Tires	Front: 24x8-12 / 25x8-12. Rear: 24x10-12 / 25x10-12.			
<b>FEATURE</b>	Electronic Power Steering (EPS)	not equipped			
	Front Light	Low Beam: halogen / High Beam: halogen / Position Light: LED Accent Light			
	Tail Light	Brake Light: LED / Position Light: LED			
	Gauge	3.5" LCD			
	Winch	2500-lbs, nylon cable			
	Hitch Type	2 in. hitch receiver			
	Steering Wheel	Adjustable tilt steering			



\* The vehicle specifications may be subject to change due to local laws and regulations in different countries and regions

		<b>CFORCE 520</b>		<b>CFORCE 520L</b>	
		<b>Homologation 167</b>	<b>Homologation 168</b>	<b>Homologation 167</b>	<b>Homologation 168</b>
<b>DIMENSIONS CAPACITIES</b>	Length x Width x Height	2186 x 1125 x 1162 mm	2386 x 1125 x 1217 mm	2186 x 1125 x 1162 mm	2386 x 1125 x 1217 mm
	Wheelbase	1260 mm	1260 mm	1460 mm	1460 mm
	Ground Clearance	262 mm	262 mm	262 mm	262 mm
	Minimum Turning Diameter	5.6m	5.6m	6.5m	6.5m
	Approach Angle	83°	83°	83°	83°
	Payload Capacity	240 kg	170 kg	240 kg	240 kg
	Curb Weight	351 kg	357 kg	365 kg	371 kg
	Hitch Towing Rating(trailer without brakes)	300 kg	150 kg	300 kg	150 kg
	Hitch Towing Rating(trailer with brakes)	652 kg	612 kg	612 kg	612 kg
	Fuel Capacity	17 L	17 L	17 L	17 L
<b>ENGINE</b>	Type	495cc, single cylinder, liquid-cooled, 4 stroke, SOHC			
	Fuel Delivery	EFI			
	Transmission	CVT, L/H/N/R/P			
	Drive System	2WD/4WD/4WD Lock			
	Power	34 hp			
<b>CHASSIS</b>	Front Suspension	Independent Dual A-Arm, 190mm travel			
	Rear Suspension	Independent Dual A-Arm, 225mm travel			
	Brakes	Four-wheels hydraulic side break + rear wheel side parking			
	Wheels	Front: 12x6.0. Rear: 12x7.5			
	Tires	Front: 24x8-12 / 25x8-12. Rear: 24x10-12 / 25x10-12.			
<b>FEATURE</b>	Electronic Power Steering (EPS)	EPS standard equipped			
	Front Light	Low Beam: LED High Beam: LED / Position Light: LED Accent Light			
	Tail Light	Brake Light: LED / Position Light: LED			
	Gauge	5" TFT			
	Winch	2500-lbs, nylon cable			
	Hitch Type	2 in. hitch receiver			
	Steering Wheel	Adjustable tilt steering			



\* The vehicle specifications may be subject to change due to local laws and regulations in different countries and regions



ACCESSORY NAME	ACCESSORY CODE	NOTE
Front Bumper Assembly	9DQV-801100-3000	/
Rear Bumper Assembly	9DQV-801300-3000	/
Front Rack Extender Assembly	9DQV-802200-3000	Apply to CFORCE 450 & 450 L
Rear Rack Extender Assembly	9DQV-802300-3000	Apply to CFORCE 450 & 450 L
Rack Extender Assembly	9DRV-802400-3000	Apply to CFORCE 520 S & 520 L
HDPE Skid Plate Assembly (8mm) - 2UP	9CQV-804200-3000	Apply to CFORCE 450 L & CFORCE 520 L
HDPE Skid Plate Assembly (8mm) - 1UP	9DQV-804100-3000	Apply to CFORCE 450 & 520
Fender Flares Assembly	9DQV-803100-3000	/
Heated Grips & Thumb Throttle Assembly	9DQV-808100-3000	Universal
Front Windshield Assembly	9DQV-805100-3000	/
Front Basket Assembly	9DQV-802100-3000	/
Cargo Box Assembly (spring latch)	9DQV-806100-3001	/
Cargo Box Assembly (lock latch)	9DQV-806100-3002	/
Whip Flag Kit	9DSV-807100-6000	Universal
CFCONNECT Seat Assembly	9DQV-809100-3000	Universal
Canvas Storage Bag	9DS#-809200-6000	Universal
Tools Box Assembly	5BYV-804100-1000	Universal
Synthetic Winch Rope	7020-800750	Universal
Tree Saver Strap	9DS#-808302-6000	Universal
Winch Rope Fairlead	7030-150701	Universal
CFMOTO Tool Holder, Pair	852114-00001	Universal
60" Plow Blade Assembly	9AWV-804300-2000	Universal
Plow Fenders, Pair	5HYV-804400-1000	Universal
Plow Markers, Pair	5HYV-806400-1000	Universal
Plow Push Tube Assembly	5HYV-804200-1000	Universal
Plow Mount Bracket Assembly	9DSV-804100-6000	Universal
CFCONNECT CLAMP KIT	9DS#-809000-6000	Universal



**UP  
YOUR  
GAME**

EXPERIENCE MORE  
TOGETHER